

BOGE S-4 Baureihe

Designed to take the lead



TECHNISCHE DATEN

BOGE Typ	Höchst- druck bar	Effektive Liefermenge m ³ /min	Nennleistung		Maße B x T x H (mm)	Druckluft- austritt DN	Gewicht schall-ge- dämmt kg	Gewicht superschall- gedämmt kg
			Haupt- antrieb kW	Lüfter- motor kW				
S 46-4 LF	7,5	2,37 - 8,38	45	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 46-4 LF	10	2,44 - 7,20	45	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 46-4 LF	13	3,33 - 5,85	45	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	7,5	2,37 - 10,69	55	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	10	2,44 - 8,70	55	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 LF	13	3,33 - 7,06	55	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 55-4 L	7,5	9,81	55	2,2	2100 x 1200 x 1720	DN 65	2030	2070
S 75-4 LF	7,5	2,37 - 13,54	75	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 LF	10	2,84 - 11,61	75	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 LF	13	3,33 - 9,50	75	2,2	2100 x 1200 x 1720	DN 65	1770	1810
S 75-4 L	10	9,52	75	2,2	2100 x 1200 x 1720	DN 65	2140	2180